



Products



Diacell® μScopeDAC-HT(S)

RELATED PRODUCTS:

- Diacell® μScopeDAC-HT(G)
- Diacell® μScopeDAC-RT(G)
- Optiprex Ruby Line
- Bohler μDriller

RELATED ACCESSORIES:

- Diacell® Design 2.5 mm Anvils
- Stainless Steel 2.5 mm Anvils Rings
- Inconel 10 mm Gasket Blanks
- Gasket Heater and Power Supply
- Ruby Powder
- Support Plates
- Gasket Indenter
- Diacell® Anvil Jigs

Diacell® μScopeDAC-HT(S)

Screw driven diamond anvil cell for high-temperature high pressures micro-spectroscopy studies.

Part of the Diacell®μScopeDAC series.

- ◆ The Diacell®μScopeDAC-HT(S) meets the need for very high pressures, compatibility with commercially available spectroscopic microscopes and high-temperatures;
- ◆ Fitted with type II as ultra-low fluorescence & ultra-low birefringence diamond anvils the cell is ideal for Infrared and Raman microscopic sample analysis;
- ◆ The Diacell®μScopeDAC-HT(S) is equipped with an internal compact gasket heater that enables research up to 600°C. Water cooling ports are also present;
- ◆ A combination of left - and right - handed screws makes sure that there is no net torque on the cell as pressure is applied;
- ◆ Maximum pressures of up to above 50 GPa are obtained with the Diacell® μScopeDAC-HT(S).

Technical Specifications:

Cell Material	Stainless Steel AISI 400C
Anvil Support Plate	Tungsten Carbide
Pressure Mechanism	Screw driven (RH and LH bolts)
Maximum Pressure	50 GPa
Top/Bottom Angles	51 ° Conical
DAC Diameter / Height	60 mm / 25 mm
Working Distance to Sample	12 mm
Numerical Aperture	0.44

Specifications subject to change without prior notice.
easyLab and Diacell are registered trademarks of Almax easyLab

www.almax-easyLab.com

Almax easyLab bv
Wagenmakerijstraat 5
8600 Diksmuide
Belgium
Ph: +32 51 55 56 37

Almax easyLab Inc (For US and Canada)
Harvard Square -1, Mifflin Place
Cambridge, MA 02138,
United States of America
Ph: + 1 617 701 7245

